First Hope

COMPLETE NOTES

Click here to visit our website

PHARMACY PRACTICAL NOTES

Complete subject and semesters are available on FirstHope app only.

Scan or click here

Click here to get the app >

Available on Google Play

JOIN THE FIRSTHOPE COMMUNITY

Join our Telegram channel

Click here to join Telegram >

Scan or click here

@FirstHopeNotes

Instagram

@firsthope.official

Click here to follow >

YouTube channel

FirstHope-Pharmacy / Live streams

Click here to watch >

WhatsApp channel

Follow FirstHope on WhatsApp

Click here to join >

FirstHope website

firsthope.co.in

Click here to visit >

B.Pharm / D.Pharm / M.Pharm / Pharm.D

Complete subjects and semesters are available in the FirstHope app.

Osmotically Controlled Drug Delivery Systems

Practical 9 - Supervised formulation and evaluation

Aim

To prepare or examine an osmotic-delivery model and relate membrane and core properties to release.

Principle

Water enters an osmotic system through a suitable semipermeable membrane because of an osmotic-pressure difference. In an elementary model, dissolved material leaves through a controlled outlet. Membrane permeability, area, thickness, core solubility and outlet design affect performance.

A formulation comparison is meaningful when the raw-material grades, batch size and evaluation conditions are recorded. Change one planned factor at a time or use a documented experimental design, and compare independently prepared batches rather than only repeated readings from one batch.

Materials and Requirements

- Approved osmotic-core formula or staff-prepared model cores
- Selected semipermeable coating material and controlled coating equipment
- Prepared outlet models and release-testing equipment
- Calibrated balance, suitable containers and identified evaluation equipment
- Controlled batch sheet and raw-data forms

Procedure

1. Define the purpose, formula, batch size, material grades and comparison conditions. Calculate all quantities before weighing.
2. Check equipment readiness and record material identities and actual quantities. Reconcile theoretical and actual batch mass.
3. Prepare the core according to the selected batch formula and record the osmotic agent and marker content.
4. Apply the approved membrane-coating process or examine staff-prepared coated cores. Record coat mass gain, thickness and visible defects.
5. Use outlets formed by the trained operator through the authorised process. Compare complete, defective and outlet-control models where provided.
6. Measure water uptake and marker release at the planned intervals, documenting membrane and outlet differences.
7. Evaluate the stated quality attributes on representative portions using the same method for all comparison batches. Record individual readings and any excluded observations with reasons.
8. Calculate the specified response, variability and material balance. Compare with predefined teaching or product criteria and discuss sources of variation.
9. Label retained preparations and dispose of remaining material through the laboratory procedure. Keep the complete preparation and evaluation record together.

Observations and Record

Enter actual measurements or the supplied teaching data. Record the method, material identity, conditions and units.

Attribute or stage	Method / conditions	Individual readings	Calculation / comment
Core and membrane identity	Record the adopted method	Record	Evaluate

Attribute or stage	Method / conditions	Individual readings	Calculation / comment
Coat mass gain / thickness	Record the adopted method	Record	Evaluate
Water uptake	Record the adopted method	Record	Evaluate
Release profile	Record the adopted method	Record	Evaluate

Calculations

• Coat mass gain (%) = (coated mass - core mass) / core mass x 100
• In a simplified membrane model, water-flow rate is proportional to membrane area and osmotic-pressure difference.

Worked Example

Illustrative core mass 300 mg and coated mass 315 mg give 5.0% coat mass gain.
If an evaluated model releases 1.5 mg marker per hour during a three-hour approximately linear interval, the released mass in that interval is 4.5 mg.
Linearity over a short interval alone does not establish an entire zero-order release mechanism.

Result and Interpretation

• Relate the observed curve to membrane integrity and the planned controls. Report any lag, leakage or blockage.
• State the preparation conditions and the evidence supporting the result. A satisfactory physical observation alone does not establish long-term stability, clinical performance or suitability for administration.

Precautions

• Use approved coating-solvent handling and ventilation.
• Outlet formation is performed by trained staff with the required guards.
• Identify models as laboratory preparations.
• Use the laboratory-approved formulation and equipment procedure. Teaching batches are identified for laboratory evaluation.

Viva Questions and Answers

What drives water entry?

The osmotic-pressure difference across the membrane.

Why inspect the coating?

Cracks or pores can create uncontrolled leakage.

Can membrane thickness affect delivery?

Yes; it changes resistance to water transport.

First Hope

COMPLETE NOTES

Click here to visit our website

PHARMACY PRACTICAL NOTES

Complete subject and semesters are available on FirstHope app only.

Scan or click here

Click here to get the app >

Available on Google Play

JOIN THE FIRSTHOPE COMMUNITY

Join our Telegram channel

Click here to join Telegram >

Scan or click here

@FirstHopeNotes

Instagram

@firsthope.official

Click here to follow >

YouTube channel

FirstHope-Pharmacy / Live streams

Click here to watch >

WhatsApp channel

Follow FirstHope on WhatsApp

Click here to join >

FirstHope website

firsthope.co.in

Click here to visit >

B.Pharm / D.Pharm / M.Pharm / Pharm.D

Complete subjects and semesters are available in the FirstHope app.